



AC Studio Flash Versalight 300

300W/S at full power. 1/4 and 1/2 power switch, 150W modeling lamp with on/off switch, synchronized slave and test trigger, 20ft. power cable and sync cord. Ideal for studio or location.

- **Guide No:** 100ft.
- **9V low volt trigger**
- **Effective slave:** 50ft.
- **Recycling time:** 1/2 - 2 sec.
- **Exposure guide:** In DIN, ASA; feet & meters
- **Wgt:** 2.8lbs
- **Reflector Dim.:** 7.1" x 4.7"



CSA300 A/C Studio Flash Versalight 300



J -110 AC Slave Flash

60W halogen modeling lamp. Built-in swivel base with umbrella hole. 1/2x full power switch. Synchronized slave and test triggering.

- **110 W/S Output**
- **Guide No:** 110 ft.
- **Effective slave:** 25ft.
- **Recycling time:** 3 - 5 seconds
- **Exposure guide:** In DIN, ASA; feet & meters



CSA360 J-110 AC Slave Flash J-110



AC Slave Bare Bulb Flash

Powered by 110 volt AC. Fits into an ordinary house socket or clamp socket. Produces a 180° light, that is subtle with soft shadows, and even throughout a large area. Triggered by on-camera flash, no cord needed. Unit has light-on indicator.

- **20 W/S Output**
- **Guide No:** 33ft.
- **Effective slave:** 33ft.
- **Recycling time:** 2 - 4 seconds
- **Exposure guide:** In DIN, ASA; feet & meters



CSA355 AC Slave Bare Bulb AS-20B



Deluxe AC Master/Slave Flash

A dual purpose unit that flashes off camera with a 9ft. cord (included) or triggered by another flash without the use of cord. Uses AC Power. Screws into a standard light socket. Ready light on unit indicates when the power is on. Fresnel diffusion.

- **45 W/S Output**
- **Guide No:** 90ft.
- **Effective slave:** 33ft.
- **Recycling time:** 2 - 4 seconds
- **Exposure guide:** In DIN, ASA; feet & meters
- **Test Button:** For manual firing



CSA350 Deluxe AC Master/Slave Flash w/Flash Cord S-45M
CSA351 Deluxe AC Slave Flash (no cord needed) S-45
CSA353 Replacement PC Cord for CSA350



Electronic Flash Meter

Compare these Features with High-Priced Units:

- Precise incident and reflected light metering with flash.
- Measuring head rotates 270° .
- Silicon Photo Diode.
- Measuring Range EV 2 to 10, precision EV ± 0.3, per 1/3 stop.
- Over/Under exposure warning.
- Aperture range F2 to F32 at ISO100.
- Displays 9 red LEDs for full stops, Yellow LED for +1/3 stop and Orange LED for +2/3 stop.
- Built-in flash trigger.
- Auto power off after 2 minutes.
- Uses 9V battery (not included).
- Includes case & wrist strap.
- Compact: 6" x 2 1/2" x 1", Lightweight: 3.3oz.



CSA580 Electronic Flash Meter

CPM/Delta Plexiglas Light Dome

Provides soft diffused lighting from any direction. Allows you to completely surround the subject with light. Highlights will appear clean white without the usual reflections of studio objects. The unique one-piece seamless construction has no glue joints or seams. Base Dia: 19 1/2" Height: 8"



CCP41010 Light Dome I, Open Top 41010

PERSONAL SERVICE IS OUR #1 PRIORITY



East: 111 Asia Place, Carlstadt, NJ 07072
West: 4055 W. Shaw Ave.#105, Fresno, CA 93722

(201) 939-7722
(559) 277-3572

FAX: (201) 939-7782
FAX: (559) 277-3574